



P/N 68012-55

Grease dispensers

Portable high-pressure 5000 ÷ 5800 psi hand-operated grease pump with 29 lbs tank, follower plate, hose 1/4" - 8' and rigid terminal with 4-jaw grease head



FLUIDS SECTORS

GREASE

AERONAUTIC | AGRICULTURE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM

Features	UM	Value
Tank capacity	lb	29
Delivery hose length	feet (')	8 -1/4"
Delivery hose	P/N	KR6802
Max grease outlet pressure	psi	5000 ÷ 5800
Capacity every 10 cycles of lever	lb	0,13
Pump	P/N	-
Compression ratio		-
Noise level	dB	-
Max working pressure	psi	-
Max air consumption	gpm	-
Capacity (free outlet 90 psi self-levelling grease at 68 °F)	lb/min	-
Grease follower plate	P/N	yes
Grease coupler	P/N	66739-55
Grease handle	P/N	-
Packing	No. - ft3	1 - 2.5
Weight	lb	23

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906