

P/N 11/12751P1NH-55

Ram hoists

Twin column ram hoist p/n 11/85-55 with industrial pump p/n 115FSP/751-55, visible air bleeder p/n 11/102-55, pneumatic controls p/n 11/130-55, electric pneumatic hybrid control p/n 11/103-55, follower plate p/n 11/64-55 for drums 400 lbs with pallet bedplate



FLUIDS SECTORS FRESH OIL | GREASE | PAINT

CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

| Features | UM | Value |
|-----------------------------------|------------|---------------|
| Flow rate | lb/min | 9,7 |
| Ratio | | 75:1 |
| Pump | P/N | 115FSP/751-55 |
| Suction tube | inches (") | ø 1.77" |
| Ram hoist | P/N | 11/85-55 |
| Follower plate | P/N | 11/60-55 |
| Follower plate adaptor | P/N | 21/64-55 |
| Pump connection hose | P/N | 996.3015-55 |
| Follower plate connection hose | P/N | 995.301-55 |
| Suitable for drums | lb | 400 |
| Pneumatic limit switch | P/N | 11/130-55 |
| Visible drain valve | P/N | 11/102-55 |
| Electric-pneumatic hybrid control | P/N | 11/140-55 |
| System pressure relief valve | P/N | 11/103-55 |
| Packing | No ft3 | 1 - 63.6 |
| Weight | lb | 628 |
| Height max/min (A-B) | inches (") | 116.2 - 76.8 |