



P/N 115FSP/751-55

Industrial pumps - s. 1200

Flanged double acting pump series 412, R 75:1 - 9.7
lbs/min, for twin ram hoist with suction tube 19.7"



FLUIDS

FRESH OIL | GREASE

SECTORS

MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate		9.7 lb/min
Ratio		75:1
Compatible fluids		high viscosity oils and greases
Suction tube upper body		carbon steel
Suction tube		carbon steel
Air inlet connection		NPT 1/2" (f)
Fluid outlet connection		NPT 1/2" (f)
Max supply pressure	psi	120
Max air consumption 120 psi	cfm	113
Noise level	dB	80
Suitable for drums or tank		pump elevator
Packing	No. - ft3	1 - 1.6
Weight	lb	35

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc