P/N 116F/121-55

Industrial pumps - s. 1200

Flanged double acting pump series 412, R 12:1 - 8 gpm, with PU seals and suction tube 37"

FLUIDS	FRESH OIL | GREASE
SECTORS	MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE
CERTIFICATIONS	ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate		8 gpm
Ratio		12:1
Compatible fluids		oils, lubricants and similar products
Suction tube upper body		carbon steel
Suction tube		carbon steel
Air inlet connection		NPT 1/2" (f)
Fluid outlet connection		NPT 3/4" (f)
Max supply pressure	psi	120
Max air consumption 120 psi	cfm	113
Noise level	dB	80
Suitable for drums or tank		suitable for drums 55 gal
Packing	No. - ft3	1 - 3.3
Weight	lb	35

RAASM USA, Inc
5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA
Phone. +1 704 370 1906 - Fax. +1 980 236 9365
Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright ® 2019 All rights reserved to RAASM USA, Inc