



P/N 116F/401-55

Industrial pumps - s. 1200

Flanged double acting pump series 412, R 40:1 - 22
lbs/min with PU seals and suction tube 37"



FLUIDS

FRESH OIL | GREASE

SECTORS

MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

| Features | UM | Value |
|-----------------------------|-----------|---------------------------------|
| Flow rate | | 22 lb/min |
| Ratio | | 40:1 |
| Compatible fluids | | high viscosity oils and greases |
| Suction tube upper body | | aluminum - carbon steel |
| Suction tube | | carbon steel |
| Air inlet connection | | NPT 1/2" (f) |
| Fluid outlet connection | | NPT 1/2" (f) |
| Max supply pressure | psi | 120 |
| Max air consumption 120 psi | cfm | 162 |
| Noise level | dB | 80 |
| Suitable for drums or tank | | suitable for drums 400 lb |
| Packing | No. - ft3 | 1 - 3.3 |
| Weight | lb | 55 |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906