P/N 120D/91-55

AISI 304 stainless steel industrial pumps

Divorced pump stainless steel AISI 304 series 412, R 9:1 - 11 gpm, with Teflon® seals



FLUIDS ANTIFREEZE | WINDSHIELD FLUID | WATER | DEF | PAINT | CLEANING DETERGENT

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

CERTIFICATIONS ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate	gpm	11
Ratio		9:1
Compatible fluids		paints, chemical and industrial fluids
Suction tube upper body		AISI 304 stainless steel
Suction tube		AISI 304 stainless steel
Air inlet connection		NPT 1/2" (f)
Fluid inlet connection		NPT 1" (f)
Fluid outlet connection		NPT 3/4" (f)
Max air consumption 120 psi	cfm	113
Noise level	dB	80
Max supply pressure	psi	120
Suitable for drums or tanks		modular
Packing	No. - ft3	1 - 2.0
Weight	lb	35

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc