



P/N 26094-55

Pneumatic pumps for oil

Air-operated pump series 200 for drums 400 lb, R 1:1 - 9.25 gpm, with Viton® seals and suction tube 37"



FLUIDS SECTORS

WASTE OIL | FRESH OIL | ANTIFREEZE | DIESEL FUEL

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

Features	UM	Value
Flow rate	gpm	9,25
Ratio		1:1
Compatible fluids		oils, lubricants and similar
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		NPT 1/4" (f)
Fluid outlet connection		NPT 3/4" (f)
Air working pressure	psi	90 ÷ 120
Average air consumption	gpm	66
Noise level	dB	81
max deliverable oil viscosity	SAE	80
Bung adaptor		standard
Suitable for drums or tanks		suitable for drums 400 lb
Packing	No. - ft ³	1 - 0.60
Weight	lb	13

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906