



P/N 2BC/16117NH5-55

Diaphragm pumps - in polypropylene and aluminum

Diaphragm pump in aluminum and polypropylene series APPB-12 with multi ported inlet/outlet, membranes in NBR, balls in Hytrel® and seats in AISI 316 stainless steel and polypropylene



FLUIDS

WASTE OIL | FRESH OIL | ANTIFREEZE | WINDSHIELD FLUID | WATER | DIESEL FUEL | DEF | PAINT | CLEANING DETERGENT

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

| Features | UM | Value |
|---------------------------------|------------|--|
| Flow rate | gpm | 15,8 |
| Ratio | | 1:1 |
| Max pressure | psi | 120 |
| Max cycles for minute | cpm | 330 |
| Delivery for cycles | gallons | 0,05 |
| Max suction lift | feet (') | dry column 15 - wet column 25 |
| Max size pumpable solids | inches (") | 0,06 |
| Max working temperature | °F | 149 |
| Noise level | dB | 75 |
| Max air consumption | cfm | 17,7 |
| Air working pressure | psi | 29 ÷ 87 |
| Air inlet connection | | NPT 3/8" (f) |
| Air outlet connection (muffler) | | NPT 1/2" (f) |
| Fluid inlet connection | | NPT 3/4" (f) (NPT 1" (f) for drum) |
| Fluid outlet connection | | NPT 1/2" (f) |
| Balls for inlet and outlet | | cylindrical ball valve |
| Membranes | | NBR |
| Balls | | Hytrel® |
| Seats | | polypropylene and AISI 316 stainless steel |
| Packing | No. - ft3 | 1 - 0.7 |
| Gross weight | lb | 13 |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906