P/N 33073-55

Pneumatic pumps for oil

Air-operated pump series 238, R 1:1 - 6 gpm with Viton® seals, suction tube 37" with bung adaptor



FLUIDS WASTE OIL | FRESH OIL | ANTIFREEZE | DIESEL FUEL

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

Features	UM	Value
Flow rate	gpm	6
Ratio		1:1
Compatible fluids		oils, lubricants and similar
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		NPT 1/4" (f)
Fluid outlet connection		NPT 1/2" (f)
Air working pressure	psi	90 ÷ 120
Average air consumption	gpm	60
Noise level	dB	81
max deliverable oil viscosity	SAE	80
Bung adaptor		standard
Suitable for drums or tanks		suitable for drums 400 lb
Packing	No. - ft3	1 - 0.60
Weight	lb	13

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

info@raasmusa.com - www.raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc