# P/N 33096-55

## Pneumatic pumps for oil

Air-operated series 238, R 1:1 - 6 gpm with Teflon® seals, suction tube 37" with bung adaptor



**FLUIDS** WASTE OIL | FRESH OIL | ANTIFREEZE | DIESEL FUEL

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

| Features | UM | Value |
|---|---|---|
| Flow rate | gpm | 6 |
| Ratio | | 1:1 |
| Compatible fluids | | oils, lubricants and similar products |
| Suction tube upper body | | aluminum |
| Suction tube | | carbon steel |
| Air inlet connection | | NPT 1/4" (f) |
| Fluid outlet connection | | NPT 1/2" (f) |
| Air working pressure | psi | 90 ÷ 120 |
| Average air consumption | gpm | 60 |
| Noise level | dB | 81 |
| max deliverable oil viscosity | SAE | 80 |
| Bung adaptor | | standard |
| Suitable for drums or tanks | | suitable for drums 400 lb |
| Packing | No. - ft3 | 1 - 0.60 |
| Weight | lb | 13 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc