

P/N 33300-55

AISI 304 stainless steel industrial pumps

Modular kit with AISI 304 stainless-steel pump for distribution from drums 55 gal, R 1:1 - 8 gpm



FLUIDS SECTORS

ANTIFREEZE | WINDSHIELD FLUID | DEF | CLEANING DETERGENT

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate	gpm	8
Ratio		1:1
Compatible fluids		suitable for antifreeze and windshield washing liquid
Suction tube upper body		AISI 304 stainless steel
Suction tube		AISI 304 stainless steel
Air inlet connection		NPT 1/4" (f)
Fluid outlet connection		NPT 1/2" (f)
Air working pressure	psi	120
Average air consumption	gpm	97
Noise level	dB	81
max deliverable oil viscosity	SAE	50
Bung adaptor		33434-55
Suitable for drums or tanks		modular
Packing	No ft3	1-1
Weight	lb	25