



P/N 33363-55

AISI 304 stainless steel industrial pumps

AISI 304 stainless steel air-operated pump series 238,
R 1:1 - 8 gpm with bung adaptor and suction tube 49.6"
for IBC tank



FLUIDS SECTORS

ANTIFREEZE | WINDSHIELD FLUID | WATER | DEF | PAINT | CLEANING DETERGENT

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING
INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY
| MINING | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate	gpm	8
Ratio		1:1
Compatible fluids		suitable for antifreeze and windshield washing liquid
Suction tube upper body		AISI 304 stainless steel
Suction tube		AISI 304 stainless steel
Air inlet connection		NPT 1/4" (f)
Fluid outlet connection		NPT 1/2" (f)
Air working pressure	psi	120
Average air consumption	gpm	97
Noise level	dB	81
max deliverable oil viscosity	SAE	50
Bung adaptor		33434-55
Suitable for drums or tanks		suitable for drums 400 lb
Packing	No. - ft3	1 - 0.7
Weight	lb	20

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906