



P/N 35061-55

Pneumatic pumps for oil

Air-operated pump series 200, R 3:1 - 5.3 gpm with Viton® seals, suitable for customizable suction tube 1" with bung adaptor



FLUIDS SECTORS

WASTE OIL | FRESH OIL | ANTIFREEZE

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

| Features | UM | Value |
|-------------------------------|-----------|---------------------------------------|
| Flow rate | gpm | 5,3 |
| Ratio | | 3:1 |
| Compatible fluids | | oils, lubricants and similar products |
| Suction tube upper body | | aluminum |
| Suction tube | | carbon steel |
| Air inlet connection | | NPT 1/4" (f) |
| Fluid outlet connection | | NPT 1/2" (f) |
| Air working pressure | psi | 90 ÷ 120 |
| Average air consumption | gpm | 92 |
| Noise level | dB | 81 |
| max deliverable oil viscosity | SAE | 130 |
| Bung adaptor | | standard |
| Suitable for drums or tanks | | customisable 1" |
| Packing | No. - ft3 | 1 - 0.35 |
| Weight | lb | 8 |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906