



# P/N 35561-55

## Pneumatic pumps for oil

Air-operated pump series 238, R:3:1 - 4.4 gpm, NBR seals, suitable for customizable suction tube 1"



### FLUIDS SECTORS

WASTE OIL | FRESH OIL | ANTIFREEZE

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

Features	UM	Value
Flow rate	gpm	4,4
Ratio		3:1
Compatible fluids		oils, lubricants and similar products
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		NPT 1/4" (f)
Fluid outlet connection		G 1/2" (f)
Air working pressure	psi	90 ÷ 120
Average air consumption	gpm	92
Noise level	dB	81
max deliverable oil viscosity	SAE	130
Bung adaptor		standard
Suitable for drums or tanks		customisable 1"
Packing	No. - ft3	1 - 0.35
Weight	lb	12

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906