P/N 35564-55

Pneumatic pumps for oil

Air-operated pump series 238, R 3:1 - 4.4 gpm, suction tube 29" with bung adaptor, suitable for 16 gal drum



FLUIDS WASTE OIL | FRESH OIL | ANTIFREEZE

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

Features	UM	Value
Flow rate	gpm	4,4
Ratio		3:1
Compatible fluids		oils, lubricants and similar products
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		NPT 1/4" (f)
Fluid outlet connection		G 1/2" (f)
Air working pressure	psi	90 ÷ 120
Average air consumption	gpm	92
Noise level	dB	81
max deliverable oil viscosity	SAE	130
Bung adaptor		standard
Suitable for drums or tanks		suitable for drums 120 lb
Packing	No. - ft3	1 - 0.49
Weight	lb	14

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc