# P/N 36076-55

## Pneumatic pumps for oil

Air-operated pump series 238, R 5:1 - 4.75 gpm, with "NBR" seals, suction tube 29" with bung adapter



**FLUIDS** WASTE OIL | FRESH OIL

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

| Features | UM | Value |
|---|---|---|
| Flow rate | gpm | 4,75 |
| Ratio | | 5:1 |
| Compatible fluids | | oils, lubricants and similar products |
| Suction tube upper body | | aluminum |
| Suction tube | | carbon steel |
| Air inlet connection | | NPT 1/4" (f) |
| Fluid outlet connection | | NPT 1/2" (f) |
| Air working pressure | psi | 90 ÷ 120 |
| Average air consumption | gpm | 92 |
| Noise level | dB | 81 |
| max deliverable oil viscosity | SAE | 240 |
| Bung adaptor | | standard |
| Suitable for drums or tanks | | suitable for drums 16 gal |
| Packing | No. - ft3 | 1 - 0.7 |
| Weight | lb | 14 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc