



P/N 36096-55

Pneumatic pumps for oil

Air-operated pump series 238, R 5:1 - 4.75 gpm, with "NBR" seals, suction tube 37" with bung adapter



FLUIDS SECTORS

WASTE OIL | FRESH OIL

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

Features	UM	Value
Flow rate	gpm	4,75
Ratio		5:1
Compatible fluids		oils, lubricants and similar products
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		NPT 1/4" (f)
Fluid outlet connection		NPT 1/2" (f)
Air working pressure	psi	90 ÷ 120
Average air consumption	gpm	92
Noise level	dB	81
max deliverable oil viscosity	SAE	240
Bung adaptor		standard
Suitable for drums or tanks		suitable for drums 55 gal
Packing	No. - ft3	1 - 0.7
Weight	lb	15

RAASM USA, Inc
5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA
Phone. +1 704 370 1906 - Fax. +1 980 236 9365
Toll free number. +1 8773701906