P/N 36161-55

Pneumatic pumps for oil

Air-operated pump series 238, R 5:1 - 5.5 gpm, with "NBR" seals, suitable for customizable suction tube 1"



FLUIDS WASTE OIL | FRESH OIL

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

Features	UM	Value
Flow rate	gpm	5,5
Ratio		5:1
Compatible fluids		oils, lubricants and similar products
Suction tube upper body		aluminum
Suction tube		carbon steel
Air inlet connection		NPT 1/4" (f)
Fluid outlet connection		NPT 1/2" (f)
Air working pressure	psi	90 ÷ 120
Average air consumption	gpm	92
Noise level	dB	81
max deliverable oil viscosity	SAE	240
Bung adaptor		standard
Suitable for drums or tanks		modular - customizable 1"
Packing	No. - ft3	1 - 0.35
Weight	lb	12

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc