# P/N 39614-55

## FCS (Fluid control system)

Pulser meter for diesel with inlet-outlet NPT 3/4" (f)




| | |
|---|---|
| FLUIDS | FRESH OIL \| ANTIFREEZE \| DIESEL FUEL |
| SECTORS | AERONAUTIC \| AUTOMOTIVE \| LUBE TRUCK AND INDUSTRIAL VEHICLE \| MANUFACTURING INDUSTRY |

| Features | UM | Value |
|---|---|---|
| Flow rate | gpm | 23,8 |
| Compatible fluids | | diesel fuel |
| Body's material | | aluminum |
| Gear's material | | POM |
| Inlet | | NPT 3/4" (f) |
| Outlet | | NPT 3/4" (f) |
| Max working pressure | psi | 1015 |
| Burst pressure | | ± 200 |
| Accuracy | | ± 0,3% |
| Pulser for gallon | | 107,1 |
| Max supply voltage | | 48 V DC max |
| Max amperage | A | 0,5 |
| Max power | W | 10 |
| Net weight | lb | 2 |
| Packing | No. - ft3 | 1 - 0.1 |
| Gross weight | lb | 2 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com


Copyright ® 2026 All rights reserved to RAASM USA, Inc