



P/N 3CA/40111HHH-55

Diaphragm pumps - entirely in aluminum

Diaphragm pump in aluminum series AAB-112 with membranes, balls and seats in Hytrel®



FLUIDS

FRESH OIL | WATER | DIESEL FUEL

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING
INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY
| MINING | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Flow rate	gpm	126,7
Ratio		1:1
Max pressure	psi	120
Max cycles for minute	cpm	220
Delivery for cycles	gallons	0,57
Max suction lift	feet (')	dry column 16 - wet column 25
Max size pumpable solids	inches (")	0,22
Max working temperature	°F	212
Noise level	dB	78
Max air consumption	cfm	120,1
Air working pressure	psi	29 ÷ 87
Air inlet connection		NPT 3/4" (f)
Air outlet connection (muffler)		NPT 1" (f)
Fluid inlet connection		NPT 2" (f)
Fluid outlet connection		NPT 1-1/2" (f)
Balls for inlet and outlet		ball valve
Membranes		Hytrel®
Balls		Hytrel®
Seats		Hytrel®
Packing	No. - ft3	1 - 2.5
Gross weight	lb	47

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906