# P/N 3CC/26111TTA-55

## Diaphragm pumps - entirely in aluminum

Diaphragm pump in aluminum series AAB-1-9 with multi ported inlet/outlet, membranes and balls in Teflon® and seats in Delrin



**FLUIDS** FRESH OIL | ANTIFREEZE | WATER | DIESEL FUEL

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

**CERTIFICATIONS** ATEX (ZONE 1) | ATEX (ZONE 21)

| Features | UM | Value |
|---|---|---|
| Flow rate | gpm | 44,9 |
| Ratio | | 1:1 |
| Max pressure | psi | 120 |
| Max cicles for minute | cpm | 300 |
| Delivery for cicles | gallons | 0,16 |
| Max suction lift | feet (') | dry column 16 - wet column 25 |
| Max size pumpable solids | inches (") | 0,12 |
| Max working temperature | °F | 212 |
| Noise level | dB | 75 |
| Max air consumption | cfm | 49,4 |
| Air working pressure | psi | 29 ÷ 87 |
| Air inlet connection | | NPT 3/8" (f) |
| Air outlet connection (muffler) | | NPT 1/2" (f) |
| Fluid inlet connection | | 4 x NPT 1" (f) |
| Fluid outlet connection | | 5 x NPT 1" (f) |
| Balls for inlet and outlet | | ball valve |
| Membranes | | PTFE |
| Balls | | PTFE |
| Seats | | Delrin |
| Packing | No. - ft3 | 1 - 1.1 |
| Gross weight | lb | 29 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc