# P/N 42090-55

## Waste oil gravity and suction drainers

Waste oil drainer with wheel-mounted 23.8 gal tank, equipped with level gauge, 3.9 gal collection bowl with oversize funnel, antisplah screen/filter and removable tool tray



**FLUIDS** WASTE OIL

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION

| Features | UM | Value |
|---|---|---|
| Tank capacity | gallons | 23,8 |
| Max draining capacity | gallons | 19,8 |
| Prechamber capacity | gallons | - |
| Bowl capacity | gallons | 3,9 |
| Air pressure for depressurisation | psi | - |
| Depressurisation time | min | - |
| Noise level | dB | - |
| Suction speed | gpm | - |
| Total suction capacity | gallons | - |
| Discharging/Suction hose | feet (') | draining 7 |
| Max pressure for discharging | psi | 7 |
| Set of probes | P/N | - |
| Packing | No. - ft3 | 2 - 10.6 |
| Weight | lb | 75 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc