P/N 43084-55

Waste oil gravity and suction drainers

Pneumatic waste oil drain with wheel-mounted 21.1 gal tank, equipped with level gauge, removable tool tray and p/n 45560-55 set of probes



FLUIDS WASTE OIL

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION

Features	UM	Value
Tank capacity	gallons	21,1
Max draining capacity	gallons	16,4
Prechamber capacity	gallons	-
Bowl capacity	gallons	-
Air pressure for depressurisation	psi	94 ÷ 102
Depressurisation time	min	2,5 ÷ 3
Noise level	dB	75
Suction speed	gpm	0.4 ÷ 0.5
Total suction capacity	gallons	15.9 ÷ 17.2
Discharging/Suction hose	feet (')	7/7
Max pressure for discharging	psi	7
Set of probes	P/N	45560-55
Packing	No. - ft3	2 - 6.7
Weight	lb	64

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc