P/N 43116-55

Fluids suction-drainers

Portable pneumatic liquid drainer with 4.3 gal tanks



FLUIDS WASTE OIL | FRESH OIL | ANTIFREEZE | DIESEL FUEL | BRAKE FLUID

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | SHIPPING AND OFFSHORE

Features	UM	Value
Tank capacity	gallons	4,2
Max draining capacity	gallons	3,4
Prechamber capacity	gallons	-
Bowl capacity	gallons	-
Air pressure for depressurisation	psi	102
Depressurisation time	min	1
Noise level	dB	75
Suction speed	gpm	-
Total suction capacity	gallons	2.4 ÷ 2.6
Discharging/Suction hose	feet (')	suction 7
Max pressure for discharging	psi	-
Set of probes	P/N	45540-55
Packing	No. - ft3	1 - 2.8
Weight	lb	22

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc