P/N 43190-55

Fluids suction-drainers

Portable pneumatic liquid drainer with 23.8 gal tanks



FLUIDS WASTE OIL | FRESH OIL | ANTIFREEZE | DIESEL FUEL | BRAKE FLUID

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | SHIPPING AND OFFSHORE

Features	UM	Value
Tank capacity	gallons	23,8
Max draining capacity	gallons	19,8
Prechamber capacity	gallons	-
Bowl capacity	gallons	-
Air pressure for depressurisation	psi	102
Depressurisation time	min	2,5 ÷ 3
Noise level	dB	75
Suction speed	gpm	-
Total suction capacity	gallons	15.9 ÷ 17.2
Discharging/Suction hose	feet (')	8 - 7
Max pressure for discharging	psi	-
Set of probes	P/N	45540-55 - 45552-55
Packing	No. - ft3	2 - 8.8
Weight	lb	70

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc