# P/N 43760-55

## Fluids suction-drainers

Waste oil drain with wheel-mounted 17.2 gal tank, equipped with 13' suction hose, special connections (p/n 45550-55 - p/n 45551-55) and p/n 45560-55 standard probe series



| | |
|---|---|
| FLUIDS | WASTE OIL |
| SECTORS | SHIPPING AND OFFSHORE |

| Features | UM | Value |
|---|---|---|
| Tank capacity | gallons | 17,2 |
| Max draining capacity | gallons | 13,7 |
| Prechamber capacity | gallons | - |
| Bowl capacity | gallons | - |
| Air pressure for depressurisation | psi | 102 |
| Depressurisation time | min | 2 |
| Noise level | dB | 75 |
| Suction speed | gpm | 0.4 ÷ 0.5 |
| Total suction capacity | gallons | 11.4 ÷ 11.9 |
| Discharging/Suction hose | feet (') | 13/7 |
| Max pressure for discharging | psi | 7 |
| Set of probes | P/N | 45560-55 |
| Packing | No. - ft3 | 2 - 8.1 |
| Weight | lb | 61 |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc