P/N 44093-55

Waste oil gravity and suction drainers

Combination pneumatic oil suction drainer 23.8 gal with transparent chamber, quick release connector and air regulator



FLUIDS WASTE OIL

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION

Features	UM	Value
Tank capacity	gallons	23,8
Max draining capacity	gallons	19,8
Prechamber capacity	gallons	2,1
Bowl capacity	gallons	3,9
Air pressure for depressurisation	psi	94 ÷ 102
Depressurisation time	min	2,5 ÷ 3
Noise level	dB	75
Suction speed	gpm	0.4 ÷ 0.5
Total suction capacity	gallons	15.9 ÷ 17.2
Discharging/Suction hose	feet (')	7/7
Max pressure for discharging	psi	7
Set of probes	P/N	45560-55
Packing	No. - ft3	3 - 12.7
Weight	lb	93

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc