



## P/N 44118-55

### Gravity drainers with pantograph and on a pit

Combination pneumatic oil suction drainer 30.4 gal with transparent chamber, quick release connector and air regulator



#### FLUIDS SECTORS

WASTE OIL

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION

| Features                          | UM        | Value       |
|-----------------------------------|-----------|-------------|
| Tank capacity                     | gallons   | 30,4        |
| Max draining capacity             | gallons   | 25,6        |
| Prechamber capacity               | gallons   | 2,1         |
| Bowl capacity                     | gallons   | 4           |
| Air pressure for depressurisation | psi       | 94 ÷ 102    |
| Depressurisation time             | min       | 3 ÷ 3,5     |
| Noise level                       | dB        | 75          |
| Suction speed                     | gpm       | 0.4 ÷ 0.5   |
| Total suction capacity            | gallons   | 22.5 ÷ 23.8 |
| Discharging/Suction hose          | feet (')  | 7/7         |
| Max pressure for discharging      | psi       | 7           |
| Set of probes                     | P/N       | 45560-55    |
| Packing                           | No. - ft3 | 3 - 16.2    |
| Weight                            | lb        | 110         |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc