P/N 45200-55

Fluids suction-drainers

Wall-mounted pump for fuel suction in accordance with ATEX directive



FLUIDS GASOLINE | DIESEL FUEL

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | SHIPPING AND OFFSHORE

CERTIFICATIONS ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Suction pump	P/N	-
Max air pressure	psi	58
Noise level	dB	81
Suitable for drums	lb	-
Suction hose length	feet (')	-
Draining hose length	feet (')	-
Suction speed	gpm	1.3 ÷ 2.6
Dolly	P/N	-
Wall bracket	P/N	33115-55
Set of probes	P/N	-
Hoses connection ø 0.2-0.3-0.4	P/N	-
Earth connection 10'		yes
Packing	No. - ft3	1 - 0.5
Weight	lb	14

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc