



P/N 45200-55

Fluids suction-drainers

Wall-mounted pump for fuel suction in accordance with ATEX directive



FLUIDS

GASOLINE | DIESEL FUEL

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Suction pump	P/N	-
Max air pressure	psi	58
Noise level	dB	81
Suitable for drums	lb	-
Suction hose length	feet (')	-
Draining hose length	feet (')	-
Suction speed	gpm	1.3 ÷ 2.6
Dolly	P/N	-
Wall bracket	P/N	33115-55
Set of probes	P/N	-
Hoses connection ø 0.2-0.3-0.4	P/N	-
Earth connection 10'		yes
Packing	No. - ft3	1 - 0.5
Weight	lb	14

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc