



P/N 45280-55

Fluids suction-drainers

Trolley mounted pump for fuel suction for drums 400 lbs in accordance with ATEX directive



FLUIDS SECTORS

GASOLINE | DIESEL FUEL

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Suction pump	P/N	33070/A-55
Max air pressure	psi	58
Noise level	dB	81
Suitable for drums	lb	400
Suction hose length	feet (')	7
Draining hose length	feet (')	7
Suction speed	gpm	1.3 ÷ 2.6
Dolly	P/N	80200-55
Wall bracket	P/N	-
Set of probes	P/N	probe ø 8 - probe ø 12
Hoses connection ø 0.2-0.3-0.4	P/N	45290-55 - 45291-55 - 45292-55
Earth connection 10'		yes
Packing	No. - ft3	2 - 4.0
Weight	lb	71

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc