



# P/N 735000-55

## Grounding cable reels - s. 350

Grounding reel series 350 fixed without cable, max cable capacity 98' - cross section 0.025 inches<sup>2</sup>



### FLUIDS

ELECTRICITY

### SECTORS

AERONAUTIC | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

### CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Information		grounding
Environment temperature	°F	23 ÷ 104
Number of conductors		1
Cable type		-
Conducting cable material		-
Conducting cable insulation		-
Cable cross section		-
Cable length	feet (')	max cable capacity 98' - cross section 0.025 inches <sup>2</sup>
Grounding pliers	P/N	-
Intensity pliers	A	-
Packing	No. - ft3	1 - 1.6
Weight	lb	23 ÷ 25

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906