P/N 8330.300-55

Hose reels - s. 290-330-390

Hose reel for hot water, 3000 psi, without hose, NPSM 3/8" (f) inlet - NPTF 3/8" (f) outlet



FLUIDS WATER | CLEANING DETERGENT

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	3000
Compatible fluids		water max 130 °C
Swivel joint		AISI 304 stainless steel
Seals		Viton®
Characteristic		fixed
Material		painted steel
Couplings		-
Hose		-
ø and hose length	ø - feet (')	-
Inlet		NPSM 3/8" (f)
Outlet		NPTF 3/8" (f)
Reel flow path		AISI 304 stainless steel - zinc plated steel
Drum width	inches (")	4.3"

RAASM USA, Inc
5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA
Phone. +1 704 370 1906 - Fax. +1 980 236 9365
Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright ® 2019 All rights reserved to RAASM USA, Inc