P/N 8390.350-55

Hose reels - s. 290-330-390

Hose reel for hot water, 3000 psi, without hose, NPSM 3/8" (f) inlet - NPTF 3/8" (f) outlet



FLUIDS	WATER
SECTORS	AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY
CERTIFICATIONS	ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	5800
Compatible fluids		water max 130 °C
Swivel joint		AISI 304 stainless steel
Seals		Viton®
Characteristic		fixed
Material		painted steel
Couplings		-
Hose		-
ø and hose length	ø - feet (')	-
Inlet		NPSM 3/8" (f)
Outlet		NPSM 3/8" (f)
Reel flow path		AISI 304 stainless steel - zinc plated steel
Drum width	inches (")	4.3"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc