# P/N 8390.352-55

## Hose reels - s. 290-330-390

Hose reel for hot water, 3000 psi, with hose 56' ø 5/16", NPTF 3/8" (m) inlet - NPTF 3/8" (m) outlet



**FLUIDS** WATER | CLEANING DETERGENT

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

**CERTIFICATIONS** ATEX (ZONE 1) | ATEX (ZONE 21)

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 5800 |
| Compatible fluids | | water max 130 °C |
| Swivel joint | | AISI 304 stainless steel |
| Seals | | Viton® |
| Characteristic | | fixed |
| Material | | painted steel |
| Couplings | | zinc plated steel |
| Hose | | 994.717-55 |
| ø and hose length | ø - feet (') | 5/16" - 56' |
| Inlet | | NPTF 3/8" (f) |
| Outlet | | NPTF 3/8" (f) |
| Reel flow path | | AISI 304 stainless steel - zinc plated steel |
| Drum width | inches (") | 4.3" |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc