P/N 8390.401-55

Hose reels - s. 290-330-390

Hose reel for oil and similar, 2000 psi, with hose 40' ø 3/8", NPTF - 1/2" (m) inlet - NPTF 1/2" (m) outlet



FLUIDS FRESH OIL | ANTIFREEZE

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	2000
Compatible fluids		oils and allied products
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		painted steel
Couplings		zinc plated steel
Hose		995.312-55
ø and hose length	ø - feet (')	3/8" - 40'
Inlet		NPTF 1/2" (f)
Outlet		NPTF 1/2" (m)
Reel flow path		zinc plated steel
Drum width	inches (")	4.3"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc