



P/N 8430.302-55

Hose reels - s. 430-440

Hose reel for hot water, 3000 psi, with hose 60' \varnothing 3/8",
NPTF 3/8" (m) inlet - NPSM 3/8" (f) outlet



FLUIDS

WATER

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND
ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

| Features | UM | Value |
|-------------------------------|--------------------------|--|
| Pressure | psi | 3000 |
| Compatible fluids | | water max 130 °C |
| Swivel joint | | AISI 304 stainless steel |
| Seals | | Viton® |
| Characteristic | | fixed |
| Material | | painted steel |
| Couplings | | zinc plated steel |
| Hose | | 995.518-55 |
| \varnothing and hose length | \varnothing - feet (') | 3/8" - 60' |
| Inlet | | NPTF 3/8" (f) |
| Outlet | | NPSM 3/8" (f) |
| Reel flow path | | AISI 304 stainless steel - zinc plated steel |
| Drum width | inches (") | 4.5" |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc