



P/N 8430.350-55

Hose reels - s. 430-440

Hose reel for hot water 5800 psi, without hose, NPSM
3/8" (f) inlet - NPSM 1/2" (f) outlet



FLUIDS

WATER

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	5800
Compatible fluids		water max 130 °C
Swivel joint		AISI 304 stainless steel
Seals		Viton®
Characteristic		fixed
Material		painted steel
Couplings		-
Hose		-
Ø and hose length	Ø - feet (')	-
Inlet		NPSM 3/8" (f)
Outlet		NPTF 1/2" (m)
Reel flow path		AISI 304 stainless steel - zinc plated steel
Drum width	inches (")	4.5"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc