

P/N 8430.400-55 Hose reels - s. 430-440

Hose reel for oil and similar, 2000 psi, without hose, NPSM 1/2" (f) inlet - NPSM 1/2" (f) outlet



FLUIDS FRESH OIL | ANTIFREEZE

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS ATEX (ZONE 1) | ATEX (ZONE 21)

| Features | UM | Value |
|-------------------|--------------|--------------------------|
| Pressure | psi | 2000 |
| Compatible fluids | | oils and allied products |
| Swivel joint | | zinc plated steel |
| Seals | | polyurethane |
| Characteristic | | fixed |
| Material | | painted steel |
| Couplings | | |
| Hose | | - |
| ø and hose length | ø - feet (') | - |
| Inlet | | NPSM 1/2" (f) |
| Outlet | | NPSM 1/2" (f) |
| Reel flow path | | zinc plated steel |
| Drum width | inches (") | 4.5" |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA Phone. +1 704 370 1906 - Fax. +1 980 236 9365 Toll free number. +1 8773701906