



P/N 8430.401/AS-55

Hose reels - s. 430-440

Hose reel for diesel fuel, suction, with hose 35' \varnothing 1/2",
NPTF 1/2" (m) inlet - NPTF 1/2" (m) outlet



FLUIDS

WASTE OIL | FRESH OIL | ANTIFREEZE

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	suction
Compatible fluids		oils and allied products
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		painted steel
Couplings		zinc plated steel
Hose		996.310-55
\varnothing and hose length	\varnothing - feet (')	1/2" - 35'
Inlet		NPTF 1/2" (m)
Outlet		NPTF 1/2" (m)
Reel flow path		zinc plated steel
Drum width	inches (")	4.5"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906