



# P/N 8430.501-55

## Hose reels - s. 430-440

Hose reel for grease, 5800 psi, with hose 40'  $\varnothing$  1/4",  
NPTF 3/8" (m) inlet - NPTF 1/4" (m) outlet



### FLUIDS

GREASE

### SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

### CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	5800
Compatible fluids		grease
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		painted steel
Couplings		zinc plated steel
Hose		993.511-55
$\varnothing$ and hose length	$\varnothing$ - feet (')	1/4" - 40'
Inlet		NPTF 3/8" (f)
Outlet		NPTF 1/4" (m)
Reel flow path		zinc plated steel
Drum width	inches (")	4.5"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc