



# P/N 8530.350-55

## Hose reels - s. 530

Hose reel for hot water, 5800 psi, without hose, NPSM  
3/8" (f) inlet - NPSM 3/8" (f) outlet



### FLUIDS

WATER

### SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND  
ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY

### CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

| Features          | UM           | Value                    |
|-------------------|--------------|--------------------------|
| Pressure          | psi          | 5800                     |
| Compatible fluids |              | water max 130 °C         |
| Swivel joint      |              | AISI 304 stainless steel |
| Seals             |              | Teflon®                  |
| Characteristic    |              | fixed                    |
| Material          |              | painted steel            |
| Couplings         |              | -                        |
| Hose              |              | -                        |
| Ø and hose length | Ø - feet (') | -                        |
| Inlet             |              | NPSM 3/8" (f)            |
| Outlet            |              | NPSM 3/8" (f)            |
| Reel flow path    |              | zinc plated steel        |
| Drum width        | inches (")   | 4.5"                     |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc