

## P/N 8530.402-55 Hose reels - s. 530

Hose reel for oil and similar, 2000 psi, with hose 80' ø 1/2", NPTF 1/2" (m) inlet - NPTF 1/2" (m) outlet



## FLUIDS FRESH OIL | ANTIFREEZE

SECTORS

FRESH OIL | ANTIFREEZE

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY

CERTIFICATIONS ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	2000
Compatible fluids		oils and allied products
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		painted steel
Couplings		zinc plated steel
Hose		996.325-55
ø and hose length	ø - feet (')	1/2" - 80'
Inlet		NPTF 1/2" (f)
Outlet		NPTF 1/2" (m)
Reel flow path		zinc plated steel
Drum width	inches (")	4.5"

## RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA Phone. +1 704 370 1906 - Fax. +1 980 236 9365 Toll free number. +1 8773701906