# P/N 8530.501-55

## Hose reels - s. 530

Hose reel for grease, 5800 psi, hose 65' ø 3/8", NPTF 3/8" (m) inlet - NPTF 1/4" (m) outlet



**FLUIDS** GREASE

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY

**CERTIFICATIONS** ATEX (ZONE 1) | ATEX (ZONE 21)

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 5800 |
| Compatible fluids | | grease |
| Swivel joint | | zinc plated steel |
| Seals | | polyurethane |
| Characteristic | | fixed |
| Material | | painted steel |
| Couplings | | zinc plated steel |
| Hose | | 995.720-55 |
| ø and hose length | ø - feet (') | 3/8" - 65' |
| Inlet | | NPTF 3/8" (f) |
| Outlet | | NPTF 1/4" (m) |
| Reel flow path | | zinc plated steel |
| Drum width | inches (") | 4.5" |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc