P/N 8534.300-55

AISI 304 stainless steel hose reels

AISI 304 stainless steel hose reel for hot water, 3000 psi, without hose, NPSM 3/8" (f) inlet - NPSM 3/8" (f) outlet



FLUIDS ANTIFREEZE | WINDSHIELD FLUID | WATER | DEF | CLEANING DETERGENT

SECTORS AGRICULTURE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

CERTIFICATIONS ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	3000
Compatible fluids		water max 130 °C
Swivel joint		AISI 304 stainless steel
Seals		Viton®
Characteristic		fixed
Material		AISI 304 stainless steel
Couplings		-
Hose		-
ø and hose length	ø - feet (')	-
Inlet		NPSM 3/8" (f)
Outlet		NPSM 3/8" (f)
Reel flow path		AISI 304 stainless steel
Drum width	inches (")	4.5"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc