P/N 8540.301-55

Hose reels - s. 540-560

Hose reel for hot water, 3000 psi, hose 100' ø 3/8", NPSM 3/8" (f) inlet - NPSM 3/8" (f) outlet



FLUIDS WATER

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

CERTIFICATIONS ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	3000
Compatible fluids		water max 130 °C
Swivel joint		AISI 304 stainless steel
Seals		Viton®
Characteristic		fixed
Material		painted steel
Couplings		zinc plated steel
Hose		995.530-55
ø and hose length	ø - feet (')	3/8" - 100'
Inlet		NPTF 3/8" (f)
Outlet		NPSM 3/8" (f)
Reel flow path		AISI 304 stainless steel - zinc plated steel
Drum width	inches (")	7.5"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc