# P/N 8540.700-55

## Various industrial hose reels

Hose reel for welding, twin hoses, 250 psi, without hose, UNF 9/16" (m) inlet - UNF 9/16" (m) outlet



**FLUIDS** OXYGEN/ACETYLENE

**SECTORS** BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

**CERTIFICATIONS** ATEX (ZONE 2) | ATEX (ZONE 22)

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 250 |
| Compatible fluids | | welding |
| Swivel joint | | brass |
| Seals | | Viton® |
| Characteristic | | fixed |
| Material | | painted steel |
| Couplings | | - |
| Hose | | - |
| ø and hose length | ø - feet (') | - |
| Inlet | | UNF 9/16" (m) |
| Outlet | | UNF 9/16" (m) |
| Reel flow path | | brass - zinc plated steel |
| Drum width | inches (") | 7.4" |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc