# P/N 8560.200-55

## Hose reels - s. 540-560

Hose reel for hot water, 1400 psi, without hose, NPSM 1" (f) inlet - NPSM 1" (f) outlet



**FLUIDS** WATER

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

**CERTIFICATIONS** ATEX (ZONE 1) | ATEX (ZONE 21)

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 1400 |
| Compatible fluids | | water max 130 °C |
| Swivel joint | | AISI 304 stainless steel |
| Seals | | Viton® |
| Characteristic | | fixed |
| Material | | painted steel |
| Couplings | | - |
| Hose | | - |
| ø and hose length | ø - feet (') | - |
| Inlet | | NPSM 1" (f) |
| Outlet | | NPSM 1" (f) |
| Reel flow path | | AISI 304 stainless steel - zinc plated steel |
| Drum width | inches (") | 14.5" |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc