



P/N 8560.301-55

Hose reels - s. 540-560

Hose reel for hot water, 3000 psi, hose 130' ø 3/8",
NPTF 3/8" (m) inlet - NPSM 3/8" (f) outlet



FLUIDS

WATER

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND
ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	3000
Compatible fluids		water max 130 °C
Swivel joint		AISI 304 stainless steel
Seals		Viton®
Characteristic		fixed
Material		painted steel
Couplings		zinc plated steel
Hose		995.540-55
ø and hose length	ø - feet (')	3/8" - 130'
Inlet		NPTF 3/8" (f)
Outlet		NPSM 3/8" (f)
Reel flow path		AISI 304 stainless steel - zinc plated steel
Drum width	inches (")	14.5"

RAASM USA, Inc
5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA
Phone. +1 704 370 1906 - Fax. +1 980 236 9365
Toll free number. +1 8773701906