



# P/N 8560.415-55

## Hose reels - s. 540-560

Hose reel for oil and similar, 725 psi, hose 100' ø 1",  
NPTF 1" (m) inlet - NPTF 1" (m) outlet



### FLUIDS

FRESH OIL | ANTIFREEZE

### SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND  
ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

### CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	psi	725
Compatible fluids		oils and allied products
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		painted steel
Couplings		zinc plated steel
Hose		998.530-55
ø and hose length	ø - feet (')	1" - 100'
Inlet		NPTF 1" (m)
Outlet		NPTF 1" (m)
Reel flow path		zinc plated steel
Drum width	inches (")	14.5"

RAASM USA, Inc  
5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA  
Phone. +1 704 370 1906 - Fax. +1 980 236 9365  
Toll free number. +1 8773701906